



Mobil 1™ 0W-30

Advanced Fuel Economy, Advanced full synthetic engine oil

Product Description

Mobil 1™ 0W-30 is an advanced full synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. Mobil 1 0W-30 meets or exceeds the requirements of the latest industry standards and outperforms our conventional oils. Mobil 1 0W-30 is recommended by ExxonMobil for SAE 0W-30, 5W-30 and 10W-30 applications.

Features and Potential Benefits

Mobil 1 0W-30 is engineered with a proprietary blend of high performance synthetic basestocks fortified with a precisely balanced additive component system. The low viscosity, fully synthetic formulation helps to increase engine efficiency and offers outstanding fuel economy. Mobil 1 0W-30 provides the high-temperature protection of 5W-30 and 10W-30 oils while offering improved fuel economy. Key features and potential benefits include:

| Features | Advantages and Potential Benefits |
|---|--|
| Low viscosity, fully synthetic formula | Helps to improve fuel economy based on 0.2-2.3% potential fuel economy improvement obtained by switching from higher viscosity oils to a 0W-30 grade. Actual savings are dependent upon vehicle/engine type, outside temperature, driving conditions and your current engine oil viscosity |
| Outstanding thermal and oxidation stability | Help to reduce oil aging resulting in long lasting protection |
| Outstanding low temperature capabilities | Quick cold weather starting and fast protection helps extend engine life |
| Precisely balanced component system | Excellent overall lubrication and wear protection performance for many driving styles and conditions, from mild to severe, where a 5W-30, 10W-30 or 0W-30 is recommended |

Applications

Mobil 1 0W-30 is recommended by ExxonMobil for SAE 0W-30, 5W-30 and 10W-30 applications in all types of modern gasoline fueled passenger cars, SUVs, vans and light trucks.

- Mobil 1 0W-30 is engineered to help deliver outstanding engine protection and improved fuel economy.
- Mobil 1 0W-30 is recommended for extreme cold conditions to help deliver quick starts and fast lubrication.
- Mobil 1 0W-30 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Specifications and Approvals

Mobil 1 0W-30 meets or exceeds the requirements of

| | |
|-------|--------------|
| ACEA | A1/B1 |
| API | SN,SM,SL,SJ |
| ILSAC | GF-5 |
| Ford | WSS-M2C946-A |

Ford WSS M2C946 A

Mobil 1 0W-30 has the following builder approvals:

| | |
|-----------------------------|--------------------------------------|
| General Motors Service Fill | dexos1™ (license number GB1C1008015) |
|-----------------------------|--------------------------------------|

According to ExxonMobil, Mobil 1 0W-30 is of the following quality level:

| | |
|----------------|----------|
| General Motors | GM 4718M |
| General Motors | GM 6094M |
| API | CF |

Typical Properties**Mobil 1 0W-30**

| | |
|--|--------|
| SAE Grade | 0W-30 |
| Viscosity @ 100°C, cSt (ASTM D445) | 10.9 |
| Viscosity, @ 40°C, cSt (ASTM D445) | 62.9 |
| Viscosity Index | 166 |
| Phosphorous (ASTM D4951) | 0.065 |
| Sulfated Ash, wt%, (ASTM D874) | 0.9 |
| HTHS Viscosity, mPa•s @ 150°C (ASTM D4683) | 3.0 |
| Flash Point, °C (ASTM D92) | 226 |
| Pour Point, °C (ASTM D97) | -50 |
| Total Base Number (ASTM D2896) | 9.1 |
| MRV @ -40 °C (ASTM D4684) | 13,250 |
| Density @15.6 °C, g/ml (ASTM D4052) | 0.842 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil , Mobil 1 and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

5-2015

Exxon Mobil Corporation
22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil.

Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2016 Exxon Mobil Corporation. All rights reserved.